

GSXR 600k 01-03 Hugger

Hugger Fitting Instructions

- Fittings: a) 1x Strap bracket for right hand swinging arm (2 piece)
b) 4x M6x16 Stainless steel allen bolts
c) 1x M6x12 Stainless steel allen bolt
d) 4x Black plastic washers
e) 1x M6 shake proof washer

General Information.

As with all huggers this model is designed to sit close to the tyre and should not be used with an oversized tyre. When fitting is complete the Hugger should sit centrally over the tyre when viewed from the rear. The tolerance in the right hand side mounting bracket allows adjustment to achieve this. As with all accessories the mountings should be checked for tightness.

The Job is easier with the bike on a paddock stand.

First remove the chainguard.

Now remove the exhaust can- a 14mm ring spanner for the four acorn nuts on the front and a 12mm ring on the foot peg mounting.

Open up the two retaining tabs to release the break hose from the swinging arm face.

With the hose clear, mount the strap bracket (a) by loosely attaching the single underside fastener (c)&(e). The bracket should be positioned up to the weld on the back brake hose tab as per the photo.

Offer up the Hugger and attach loosely to the chain side using 2x (b) and (d)

Attach to the right side bracket using 2x (b) and 2x (d).

NOTE. Both fingers of the bracket should be inside the Hugger.

Fully tighten all fasteners checking left/right alignment over the tyre as you do so.

Re-tighten the rear break hose mounting clip.

Check position of hugger over tyre. If adjustment is required loosen all fasteners slightly to allow re-alignment.

